

SNOWREX PSL INDICATOR



FEATURES

- IP67 WATERPROOF(PSL SST)
- LARGE LCD DISPLAY
- UP TO 1/15,000 DISPLAY RESOLUTION (INTERNAL 1/300,000)
- HI/LO WEIGHT CHECK
- POWER: BUILT-IN RECHARGEABLE BATTERY(6V/4Ah)
OR AC ADAPTER
- ANTI-RFI/EMI
- AUTO POWER OFF
- APPLICATION:PLATFORM SCALE, PALLET SCALE,

FORK LIFT SCALE , LIVE STOCK SCALE

- KILOGRAM (KG) AND POUND (LB) WEIGHING MODES
- RS232 OR SERIAL PRINTER OUTPUT
- ADJUSTABLE GRAVITY VALUE
- SET POINT(OPTION)

OPTION

- RS-232 INTERFACE
- SUPPORT FRAME (PSL SST)
- WALL MOUNTING (PSL ABS)
- ROTATE STRUCTURE (PSL ABS)
- JUNCTION BOX
- IP67 ACCESSORIES (PSL SST)

SPECIFICATIONS

MODEL	PSL
DISPLAY RESOLUTION	3,000 / 5,000 / 6,000 / 7,500 / 10,000 / 12,000 / 15,000 / 30,000... SELECTABLE DIVISIONS
INTERNAL RESOLUTION	300,000 COUNTS
LOADCELL EXCITATION	+5V DC
INPUT SENSITIVITY	0.5u V/D
MAX. MEASUREMENT VOLTAGE	10 mV
DISPLAY	LCD ; HEIGHT: 52MM ; WEIGHT: 5 ½ DIGITS
ENVIRONMENT LIMITS	0~40°C ; RH LESS THAN 85%
POWER SUPPLY	9V/500 MA , DC ADAPTER ; BUILT IN 6V/4Ah RECHARGEABLE BATTERY
LOADCELL DRIVE CAPACITY	UP TO 4 LOADCELLS AT 350 Ω LOADCELL
NON-LINEARITY	0.02 % OF FULL SCALE
A/D RESOLUTION	500,000 COUNTS (MAX)
DIMENSIONS	ABS 235 x 160 x 115(mm) SST 240 x 100 x 194(mm)

PRODUCT CONCEPT

- IP67



Have strong **waterproof and dustproof** function that can totally protected against dust and protected against the effects of temporary immersion between 15cm and 1m. Duration 30 mins. Due to the mention it can apply to various platform.

- BIG SIZE DISPLAY



Clearer measure data shows on **the BIG SIZE Display** (word height: 52mm) that users can read the measure data far from the indicator

LEAD TIME

- 2 MONTHS AFTER RECEIVE ORDER (PSL SST)
- 1 MONTH AFTER RECEIVE ORDER (PSL ABS)